

The VM-12HDCP is an HDCP-compliant distribution amplifier for DVI-D signals with resolution up to 1080p or UXGA. It reclocks and equalizes the signal and distributes it to twelve identical outputs

FEATURES

Max. Data Rate - 4.95Gbps (1.65Gbps per graphic channel)

HDTV Compatible

HDCP Compliant

HDMI Support - HDMI Compressed Audio Channels

Kramer Equalization & reKlocking™ Technology - Rebuilds the digital signal to travel longer distances

I-EDIDPro™ Kramer Intelligent EDID Processing™ - Intelligent EDID handling & processing algorithm ensures Plug and Play operation for DVI systems

Active Input & Output LED Indicators

Worldwide Power Supply - 100240V AC

TECHNICAL SPECIFICATIONS

INPUT:	1 DVID on a DVII connector, 1.2Vpp; DDC signal 5Vpp (TTL)
OUTPUTS:	12 DVID on DVII connectors, 1.2Vpp; DDC signal 5Vpp (TTL)
BANDWIDTH:	4.95Gbps (1.65Gbps per graphic channel)
CONTROLS:	SELECT and READ buttons for selecting and storing EDID information
POWER CONSUMPTION:	100240V AC, 50/60Hz, 11VA
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F)
STORAGE TEMPERATURE:	40° to +70°C (40° to 158°F)
HUMIDITY:	10% to 90%, RHL noncondensing
PRODUCT DIMENSION:	19" x 9.34 x 1U (43.6cm x 23.72cm 4.36cm) W, D, H
PRODUCT WEIGHT:	2.1kg (4.6lbs) approx
SHIPPING DIMENSION:	52.50cm x 33.00cm x 10.70cm (20.67" x 12.99" x 4.21") W, D, H
SHIPPING WEIGHT:	3.0kg (6.5lbs) approx
INCLUDED ACCESSORIES:	Power cord, rack "ears"