

# VM-24HDCP

2x1:4 DVI (HDCP) Distribution Amplifier

| DVI

The VM-24HDCP is a high-performance distribution amplifier for DVI signals. The unit reclocks and equalizes one of two input signals and distributes it to four identical outputs

## FEATURES

Max. Data Rate - 6.75Gbps (2.25Gbps per graphic channel)

HDTV Compatible

HDCP Compliant

HDMI Support - HDMI Compressed Audio Channels

I-EDIDPro™ Kramer Intelligent EDID Processing™ - Intelligent EDID handling & processing algorithm ensures Plug and Play operation for DVI systems

Control - Front panel & IR switching

Worldwide Power Supply - 100240V AC

Standard 19" Rack Mount Size - 1U. Rack "ears" included

## TECHNICAL SPECIFICATIONS

---

INPUTS:	2 DVI, 1.2Vpp on a DVI Molex 24pin (F) connector; DDC signal 5Vpp (TTL)
OUTPUTS:	4 DVI, 1.2Vpp on DVI Molex 24pin (F) connectors; DDC signal 5Vpp (TTL)
MAX. DATA RATE:	6.75Gbps (2.25Gbps per graphic channel)
CONTROLS:	EDID SELECT, EDID READ, IN 1, IN 2 buttons, RS232, IR
INDICATOR LEDs:	OUTPUT STATUS LEDs
POWER CONSUMPTION:	100240V AC, 50/60Hz 17VA
INCLUDED ACCESSORIES:	Power cord, rack "ears", nullmodem adapter, Windows®based control software, infrared remote control transmitter
PRODUCT DIMENSION:	19" x 7.20 x 1U (43.6cm x 18.30cm 4.36cm) W, D, H
PRODUCT WEIGHT:	1.5kg (3.3lbs) approx
SHIPPING DIMENSION:	55.00cm x 27.60cm x 10.70cm (21.65" x 10.87" x 4.21" ) W, D, H
SHIPPING WEIGHT:	2.3kg (5.1lbs) approx