The VM-4HDCPxI is a high-performance distribution amplifier for DVI signals. The unit reclocks and equalizes one input signal and distributes it to four identical outputs

FEATURES

Max. Data Rate - 6.75Gbps (2.25Gbps per graphic channel)

Max. Resolution - Up to UXGA & 1080p

HDTV Compatible

HDCP Compliant

I-EDIDPro™ Kramer Intelligent EDID Processing™ - Intelligent EDID handling & processing algorithm ensures Plug and Play operation for DVI systems

Worldwide Power Supply - 100240V AC

Standard 19" Rack Mount Size - 1U. Rack "ears" included

TECHNICAL SPECIFICATIONS

INPUT: 1 DVI, 1.2Vpp on a DVI Molex 24pin (F) connector; DDC signal 5Vpp (TTL)

OUTPUTS: 4 DVI, 1.2Vpp on DVI Molex 24pin (F) connectors; DDC signal 5Vpp (TTL)

MAX. DATA RATE: 6.75Gbps (2.25Gbps per graphic channel)

CONTROLS: EDID SELECT, EDID READ

INDICATOR LEDs: **OUTPUT STATUS LEDs**

POWER CONSUMPTION: 100240V AC, 50/60Hz 17VA

INCLUDED

Power cord, rack "ears" ACCESSORIES:

PRODUCT 19" x 7.20 x 1U (43.6cm x 18.30cm 4.36cm) W, D, H

DIMENSION:

PRODUCT WEIGHT: 1.5kg (3.2lbs) approx

SHIPPING 55.00cm x 27.60cm x 10.70cm (21.65" x 10.87" x 4.21") W, D, H

DIMENSION:

SHIPPING WEIGHT: 2.2kg (4.9lbs) approx