

**PDP-42MXE20**[Print pagina](#) | [Home](#) | [terug](#)**42-inch "Pureblack Panel 2" Screen**

Belangrijke kenmerken	PDP-42MXE20
Schermformaat	42-Inch
Hoogte-breedteverhouding	16:9
Aantal pixels (hor x ver)	1024 x 768
Helderheid	1100 cd/m ²
Contrastverhouding	3000:1
PUREBlack Panel 2	Ja
PUREDrive Pro	Ja
Diepwafelribstructuur	Ja
i-CLEAR Drive	Ja
Knippervrij beeld	Ja
Afmetingen (B x H x D)	1022 X 610 X 98 mm
Gewicht	30.5 kg
Connectivity	PDP-42MXE20
PC-ingang 1	Mini D-sub 15 -pin, RGB/YUV signal (Sync on Green compatible)
PC-ingang 2	DVI-D 24-pin Digital RGB signal (DVI compliant TDMS. HDCP compliant)
PC-ingang 3	Analogue 5 x BNC (PDA5003)
Audio-ingang connector	Stereo Mini
Audio-uitgang connector	Stereo Mini
Luidsprekeruitgang x 2 (L/R)	Ja
Videosignalen	3,58NTSC, 4,43NTSC, PAL, PAL M, PAL 60, SECAM (PDA-5003/PDA-5004)
Optionele videokaarten	PDA-5003 / PDA-5004

Video-ingang connector	Input 1 supports RGB/YUV, Input 2 supports RGB
Beeld	PDP-42MXE20
Effectief schermformaat	921.6 X 515.3 mm (42-inch diagonal)
Pixel pitch	0.9 (Hor./RGB trio) x 0.671(Ver.) mm
Kijkhoek	More than 160 ° (Hor) / More than 160 ° (Ver)
Screensaver functies	Seamless Orbiter mode, Inverse mode, Full mask, soft focus
WHQL-compatibel	Ja
Installer en Operator kenmerken	PDP-42MXE20
Professionele kenmerken	● Intelligent Auto Setup ● Point Zoom ● Colour Detail Adjustment ● Energy Save Modes ● Multi Language OSD ● IR and Keylock ● LED OFF Mode ● Smart Cooling System ● 10 event Timer Feature ● Integrator Menu ● RS-232C Features ● FRC Feature ● Broadcast Modes
Multi Screen functies	● Picture and Picture: Split-Screen ● Picture-in-Picture: Small picture can be moved to any of the four corners. 4 Sizes, 0 to 80% transparency, Auto PiP detect mode, PiP Fade. ● Picture-out-Picture: Banner Mode (10 settings)
Intergrator mode	Ja
RS-232C Interface	Ja
Combination in/out	Ja
Video Wall Modes	2 x 2 mode, 3 x 3 mode, 4 x 4 mode, 5 x 5 mode
Monitor functions	Ja
Expansion slot	2 (Video and Communication slot)
Algemene kenmerken	PDP-42MXE20
Stroomverbruik	285W (1.2W Standby)
Stroomvereisten	AC 100 ~240 V ±10 %, 50/60 Hz
Gebruikstemperatuur	0 °C ~ 40 °C
Vochtigheidsgraad bij gebruik	20 % ~ 80 %
Veiligheidsvoorschriften	Low Voltage Directive (73/23/EEC, ammended by 93/68/EEC), EMC Directives (89/336/EEC, ammended by 92/31/EEC and 93/68/EEC).

Wilt u dit product kopen?

Neem dan contact op met **een Pioneer verkooppunt** in uw buurt!

Voor meer informatie over prijs en beschikbaarheid kan je ook contact opnemen met ons **kantoor**.

[Print pagina](#) | [Home](#) | [terug](#)

[Home](#) • [Algemene Voorwaarden](#) • [Privacybeleid](#) | © Pioneer