

**PDP-60MXE20**[Print pagina](#) | [Home](#) | [terug](#)**60-inch "Pureblack Panel 2" Screen**

Belangrijke kenmerken	PDP-60MXE20
Schermformaat	60-Inch
Hoogte-breedteverhouding	16:9
Aantal pixels (hor x ver)	1365 x 768
Helderheid	1000cd/m ²
Contrastverhouding	4000:1
PUREBlack Panel 2	Ja
PUREDrive Pro	Ja
Diepwafelribstructuur	Ja
i-CLEAR Drive	Ja
Knippervrij beeld	Ja
Afmetingen (B x H x D)	1470 x 880 x 122 mm
Gewicht	62 kg
Connectivity	PDP-60MXE20
PC-ingang 1	Mini D-sub 15 -pin, RGB/YUV signal (Sync on Green compatible)
PC-ingang 2	DVI-D 24-pin Digital RGB signal (DVI compliant TDMS. HDCP compliant)
PC-ingang 3	Analogue 5 x BNC (PDA5003)
Audio-ingang connector	Stereo Mini
Audio-uitgang connector	Stereo Mini
Luidsprekeruitgang x 2 (L/R)	Ja
Videosignalen	3,58NTSC, 4,43NTSC, PAL, PAL M, PAL 60, SECAM (PDA-5003/PDA-5004)
Optionele videokaarten	PDA-5003 / PDA-5004

Video-ingang connector	Input 1 supports RGB/YUV, Input 2 supports RGB
Beeld	PDP-60MXE20
Effectief schermformaat	1318.6 x 741.9 mm (60-inch diagonal)
Pixel pitch	0.966 (Hor./RGB trio) x 0.966(Ver.) mm
Kijkhoek	More than 160 ° (Hor) / More than 160 ° (Ver)
Screensaver functies	Seamless Orbiter mode, Inverse mode, Full mask, soft focus
WHQL-compatibel	Ja
Installer en Operator kenmerken	PDP-60MXE20
Professionele kenmerken	● Intelligent Auto Setup ● Point Zoom ● Colour Detail Adjustment ● Energy Save Modes ● Multi Language OSD ● IR and Keylock ● LED OFF Mode ● Smart Cooling System ● 10 event Timer Feature ● Integrator Menu ● RS-232C Features ● FRC Feature ● Broadcast Modes
Multi Screen functies	● Picture and Picture: Split-Screen ● Picture-in-Picture: Small picture can be moved to any of the four corners. 4 Sizes PiP, 0 to 80% transparency, Auto PiP detect mode, PiP Fade. ● Picture-out-Picture: Larger image is true XGA. Banner Mode (10 settings)
Intergrator mode	Ja
RS-232C Interface	Ja
Combination in/out	Ja
Video Wall Modes	2 x 2 mode, 3 x 3 mode, 4 x 4 mode, 5 x 5 mode
Monitor functions	Ja
Expansion slot	2 (Video and Communication slot)
Algemene kenmerken	PDP-60MXE20
Stroomverbruik	450W (0.8W Standby)
Stroomvereisten	AC 100 ~240 V ±10 %, 50/60 Hz
Gebruikstemperatuur	0 °C ~ 40 °C
Vochtigheidsgraad bij gebruik	20 % ~ 80 %
Veiligheidsvoorschriften	Low Voltage Directive (73/23/EEC, ammended by 93/68/EEC), EMC Directives (89/336/EEC, ammended by 92/31/EEC and 93/68/EEC).
Accessoires inclusief	Power Cord, Remote Control Unit, 2 x AA (R6) batteries, Cleaning Cloth (for screen), Speed Clamps, Bead bands, Ferrite cores (for power cord), ferrite cores (for audio cables), cable tie, Operating Instructions (CD Rom), Start up Guide

Wilt u dit product kopen?

Neem dan contact op met **een Pioneer verkooppunt** in uw buurt!

Voor meer informatie over prijs en beschikbaarheid kan je ook contact opnemen met ons **kantoor**.

[Print pagina](#) | [Home](#) | [terug](#)

[Home](#) • [Algemene Voorwaarden](#) • [Privacybeleid](#) | © Pioneer