

PLC-XF45

Brilliant Ideas for Great Images.

SANYO

- Brightness: 10,000 ANSI lumens
- XGA Resolution
- Contrast 1,100 : 1
- Horizontal and vertical lens shift function
- 10 interchangeable lenses, 8 adapter boards
- Four lamp system
- Network integration (optional)
- Real Color Management



PLC-XF45

Brilliant Ideas for Great Images.



TECHNICAL DETAILS

PLC-XF45

Category	Professional
Panel	3 x 1.8" TFT p-Si (Microlens)
Lamp	4 x 250 W UHP
Brightness ANSI lumens	10,000
Lamp Service Life	1,000 Hours
Standard Lens	Depending on lens (delivery does not include lens)
Aspect Ratio	Depending on lens
Distance	Depending on lens (delivery does not include lens)
Contrast Ratio	1,100 : 1
Resolution in pixels	1,024 x 768 (XGA)
Horizontal Resolution	800 TV lines
Uniformity	90 %
Bandwidth / Frequency	230 MHz, horizontal 15 ~ 120 kHz, vertical 50 ~ 120 Hz
Color Systems	PAL, SECAM, NTSC, NTSC4.43, PAL-M/N
Connections	Input 1: DVI-I (digital/analog), Audio: 2x Cinch (R/L-mono); Control Input: Mini-DIN 8-pin (RS232) Input 2: 5x BNC (RGBHV and Y/Pb-Cb/Pr-Cr), Audio: 2x Cinch (R/L-mono); Control Input: Mini-DIN 8-pin (RS232) Input 3: 2x BNC (Composite and Y/C); Mini-DIN 4-pin (S-Video), Audio: 2x Cinch (R/L-mono) Input 4: D-Sub15 (RGB), Audio: 2x Cinch (R/L-mono); Control Input: Mini-DIN 8-pin (RS232) Audio Output: 2x Cinch (R/L-mono) Control Input 1: D-Sub9 (RS232) Control Input 2: USB Typ B (mouse control) Control Input 3: 3.5 mm Stereo Jack (cable remote control) Control Output: D-Sub9 (RS232)
Audio	3 W Stereo
Keystone Correction	vertical + 40° / - 20°
Lens-Shift	10 : 0 - 0 : 10 vertical (applies to LNS-S02) 1 : 1 vertical / 1 : 1 horizontal (applies to LNS-W03) 1 : 8 - 8 : 1 vertical (applies to all other lenses) 2 : 3 - 3 : 2 horizontal (applies to all other lenses)
HDTV Signals	720p / 1,035i / 1,080i (HDTV-compatible)
Computer Compatibility	U-XGA / S-XGA / XGA / S-VGA / VGA / Mac
Zoom / Focus	Depending on lens
Power Consumption	1,500 W / 100 - 240 V
Warranty	3 Years Warranty
Dimensions (W x H x D) in mm	581 x 252 x 783
Weight	37 kg
Standard Accessories	IR remote control with laser pointer and mouse function, batteries, operating manual, computer cable (D-Sub15/D-Sub15), Mac/VGA-Adapter, mouse cable (PS/2, Mac, serial), DVI-cable, DVI/VGA-Adapter, dust cover, power cable, Real Colour Manager Software
Optional Accessories	8 optional adapter boards: DVI-I-Board (POA-MD18DVI); 5 BNC-Board (POA-MD16VD1); Y/C-Board (POA-MD03VD2A); D-Sub15-Board (POA-MD04VGA); HD-SD-SDI-Board (POA-MD17SDI); Progressive Video-Board (POA-MD09VD3); Network-Board (POA-MD13NET2); SDI-Board (POA-MD15SDI)
Lenses	10 Interchangeable lenses Optional Telephoto Zoom lenses: LNS-W01Z, LNS-W02Z, LNS-W03, LNS-W04 Optional Standard lenses: LNS-S03, LNS-S02Z Optional Tele lenses: LNS-M01Z, LNS-T01Z, LNS-T02, LNS-T03

For more information about optional accessories, please see the "Network Solutions and Accessories" brochure.



Technical specifications are subject to change without notice. Status 02/2005

